Table B-18. Site Investigations and Monitoring at Waste Management Facilities in the R-Area Geographic Groupinga

Facility	RCRA monitoring wellb	Site investigations ^C	Monitoring results
		HAZARDOUS WASTE SITES	
R-Area burning/rubble pits (131-R, 131-1R)	RRP 1 RRP 2 RRP 3 RRP 4	Wells monitored quarterly for RCRA and SCHWMR parameters. Waste sediment characterization program to be conducted.	Statistical analysis of groundwater monitoring data indicates the following parameters to be present: Sodium Copper
R-Area acid/caustic basin (904-77G)	RAC 1 RAC 2 RAC 3 RAC 4	Wells monitored quarterly for RCRA and SCHWMR parameters. Waste site characterization program completed by third quarter of 1985.	Statistical analysis of groundwater monitoring data indicates the following to be present: Conductivity Chloride Total dissolved solids Sodium Sediment samples showed metals and other inorganics to be present.
		LOW-LEVEL WASTE SITES	
R-Area Bingham Pump outage pits (643-8G, G43-9G, 643-10G)	None	No monitoring wells exist at outage pits, and records yield no evidence of core-sampling activity there. Radioactivity in vegetation measured in 1970.	Vegetation growing above outage pits shows little or no elevation in activity levels.
R-Area seepage basins (904-57G, 904-58G, 904-59G, 904-60G, 904-103G, 904-104G)	48 monitoring wells asso- ciated with R-Area reactor seepage basinsd	Wells typically monitored for gross alpha, gross nonvolatile beta, and tritium. Soil borings were analyzed from sediment in and beneath backfilled basins in 1978.	Groundwater constituents include

aSources: Huber, Johnson, and Marine, 1987; Ward, Johnson, and Marine, 1987; Pekkala, Jewell, Holmes, and Marine, 1987a, b. bThe monitored hydrolgeologic unit for these wells is the Barnwell.

CSee page B-1.
dNot RCRA monitoring wells.